



接點示意圖:

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
,	,
,	,
,	,
34	34
(地線) 35	35
36	36
(白色) 37	37
38	38
(綠色) 39	39
40	40

⑦	醋酸膠布	1PCS	黑色 W50MM*L80MM
⑥	拉帶	1PCS	白色 W25*L50MM
⑤	拉帶	1PCS	白底黑字 W25*L50MM
④	熱縮套管	2PCS	黑色 \varnothing 3MM*10MM
③	插頭	2PCS	IDC 40P 黑色 有耳 無塞 三件 PH:1.27*2.54MM
②	線材	1PCS	USB 2.0 30AWG*1PR PVC(GREEN,WHITE ID:0.6MM) AL/MY+地線 OD:2.7MM 黑色圓線 L=260MM
①	線材	1PCS	UL2678 30AWG 40C PH:0.635MM 灰色排線 L=255MM (每20Pin分線)
NO.	NAME	Q'TY	DESCRIPTION

Test Condition
 1.100% Open/Short
 2.Contact Resistance:5m Ohm Max
 3.Insulation Resistance:2M hom Min
 4. HI-POT: 300V

注:
 排線兩端第35PIN,37PIN,39PIN需剪斷, USB芯線及地線用30AWG排線焊接,並套上熱縮套管

1.3			
1.2			
1.1			
1.0	RELEASED	Cel Wang	07-Dec-2006
REV.	ECN. NO.	DR.BY	DATE



MATL.: FINISH:

X.: ± 0.30	X': $\pm 5.0^\circ$	TITLE: 40P-40P IDC Connector Assembly		A4
X.X: ± 0.20	X.X': $\pm 3.0^\circ$	APPD:		
X.XX: ± 0.15	X.XX': $\pm 1.0^\circ$	PRAT NO: ASS-C-520		
UNIT: mm		CHKD:		
SCALE: 1:1	SHEET: 1/1	DWG. NO.: 20061207-01(HK)		
		DR.: Cel Wang		
		REV.: 1.0	DATE: 07-Dec-2006	