



接點示意圖:

P1 (BLUE)	P2 (GRAY)	P3 (BLACK)
1	1	1
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
.	.	.
.	.	.
18	18	18
(第20Pin塞Key) 20	20	20
21	21	21
23	23	23
25	25	25
27	27	27
28	28	28
29	29	29
31	31	31
32	32	32
33	33	33
.	.	.
34	34	34
35	35	35
36	36	36
37	37	37
38	38	38
39	39	39

GROUND PIN

2	2	2
19	19	19
22	22	22
24	24	24
26	26	26
30	30	30
34	40	40
40		

⑥	PET网	百海	2PCS	紅色雙股 $\varnothing 8.0\text{MM}$
⑤	鴨舌套	德聯	4PCS	PVC 透明紅色 $\varnothing 11.5\text{MM}$
④	插頭	佳霖	1PCS	ATA 40P 有耳 有塞 黑色 三件 (第20Pin塞Key)
③	插頭	佳霖	1PCS	ATA 40P 有耳 有塞 灰色 二件 (第20Pin塞Key)
②	插頭	佳霖	1PCS	ATA 40P 有耳 有塞 藍色 三件 (第20Pin塞Key)
①	線材	越洋	1PCS	UL20276 30AWG 40PRS(1PR:RED/WHITE,39PRS:COLOR) 彩色芯線 L=520MM
NO.	NAME	VENDER	Q'TY	DESCRIPTION

Test Condition
 1.100% Open/Short
 2.Contact Resistance:5m Ohm Max
 3.Insulation Resistance:5M hom Min
 3. HI-POT: 300V 10MS.

1.3			
1.2			
1.1			
1.0	RELEASED	Cel Wang	07-Dec-2006
REV.	ECN. NO.	DR.BY	DATE



MAT'L:	FINISH:
--------	---------

x.: ± 0.30	x': $\pm 5.0'$	TITLE :	A4
x.x: ± 0.20	x.x': $\pm 3.0'$	40P-40P IDC Connector Assembly	
x.xx: ± 0.15	x.xx': $\pm 1.0'$	APPD.:	PRAT NO : ASS-C-522
UNIT: mm		CHKD.:	DWG. NO.: 20061207-03(HK)
SCALE: 1:1	SHEET: 1/1	DR.: Cel Wang	REV.: 1.0 DATE: 07-Dec-2006